




DIGITAL DISCUSSION CONTROL UNIT MCW-D 50



FEATURES

- Central control unit to control up to 4096 digital wireless microphone units of the MCW-D 5xx series
- Specific DSSS modulation (Direct Sequence Spread Spectrum) ensures a high noise immunity when used with other wireless systems in the 2.4 GHz frequency band
- Wireless transmission in the world-wide approved frequency range of 2.4 GHz
- Maximum security against unauthorised listening:
 - Proprietary data format
 - 128 bit-encryption key
 - Optional entry of a freely definable eight-digit key for control unit and microphone units. Microphone units with a wrong key will be recognised and deactivated immediately.
- Can easily be updated with Field Programming Technology
- Up to 9 channels for audio transmission
- Depending on the version a maximum of three (e.g. 2 delegates and 1 chairman) or nine microphone units (e.g. 7 delegates and 2 chairmen) can be allocated simultaneously
- Integrated antenna splitter/combiner for diversity reception
- Digital limiter function per input channel (can be configured)
- Manual, Push-To-Talk, Override or Voice Activated mode
- RS 232 interface for external operation with PC or media control
- Network connection (TCP/IP) for external operation via PC or media control system
- MCW-D 50 Conference software for Windows® to configure the control unit and microphone units and control of the conference under Windows®
- Remote RF-receiving and transmitting antennae for large distances
- Quick setup for discussions without additional sound contracting devices
- Due to RF operation no extensive installations for transmitter or receiver components necessary (compared to infrared technology)
- Additional audio input for e.g. wireless microphones
- Recording output for documentation
- Master output for external sound contracting systems
- All connections are plug-in type
- 19" desktop housing, 2 HU

VERSIONS

MCW-D 50-3	Control unit with 1 RF module/3 channels	Order # 479.705
MCW-D 50-9	Control unit with 3 RF modules/9 channels	Order # 481.560

Germany

Theresienstr. 8
D-74072 Heilbronn
Tel. +49 (0)71 31 / 6 17-0
Fax +49 (0)71 31 / 617-224
E-mail: info@beyerdynamic.de
Internet: www.beyerdynamic.de

United States

56 Central Ave.
Farmingdale, NY 11735
Tel. +1 (631) 293-3200
Fax +1 (631) 293-3288
E-mail: salesUSA@beyerdynamic.com
Internet: www.beyerdynamic.com

Great Britain

17 Albert Drive
Burgess Hill RH15 9TN
Tel. +44 (0)1444 / 258 258
Fax +44 (0)1444 / 258 444
E-mail: sales@beyerdynamic.co.uk
Internet: www.beyerdynamic.co.uk

DESCRIPTION

Digital control unit for an almost unlimited number of wireless microphone units with loudspeaker. Integrated diversity combiner for a maximum of 3 or 9 smart link receiving modules. Depending on the version of the MCW-D 50 control unit a maximum of 3 (e.g. 2 delegates and 1 chairman) or 9 microphone units (e.g. 7 delegates and 2 chairmen) can be activated simultaneously.

There is a constant status inquiry, monitoring or control due to the data connection to the microphone units. Individual microphone units can be activated via the RS 232 serial interface. The complete discussion system can be switched off via a control command or by pressing the "Stand-by" button on the front. The 9 LEDs on the front indicate the assigned transmission channels of the microphones. To increase the security of the system, the control unit can operate in the "security mode" i.e. the control unit only operates with microphone units which have the same encryption key. In addition to this, the audio data are encrypted.

TECHNICAL SPECIFICATIONS

General


Frequency range	2400 - 2483.5 MHz (ISM-band)
Modulation	Direct Sequence Spread Spectrum DSSS, digital signal processing acc. to own standard
Max. number of audio streams	9 useable channels per system
Signal-to-noise ratio	80 dB typ., (unweighted signal-to-noise ratio)
Range between microphone units and control unit	> 100 m
Power supply	110 - 240 V AC 50/60 Hz
Approval	world-wide

MCW-D 50 Control Unit

Frequency response	70 Hz - 10 kHz (-3 dB)
Operation mode	Diversity (receiver), separate for each channel
Antenna connection	3 N-connectors (female)
Remote supply voltage for antenna amplifier	5 V, max. 2 A
Transmitting power	max. 15 dBm per channel (average, duty cycle ≤ 30%)*
Connections	
Serial control port	RS 232
Ethernet port	LAN, TCP/IP standard
Master output balanced	XLR, +6 dBu
Master output unbalanced	RCA, level adjustable (1.55 V - 300 mV range)
Input balanced	XLR, +6 dBu, switchable
Input unbalanced	RCA, (min. 500 mV for max. level), +15 dBu, -10 dBu, switchable
Power supply	110 - 240 V AC 50/60 Hz
Fuse	2 x 3.15 A (slow blow)
Power consumption	20 W (without antenna amplifiers)
Temperature range	+10° - +40°C (at < 90% humidity)
Indication	9 channel LEDs (red/green) and Power LED (red/green)
Min. depth of Rack	380 mm
Dimensions (W x H x D)	19", 2HU (440 x 88 x 310 mm)
Weight	4.7 kg

*The transmitter power can differ from this value due to specific regulations in various countries.

MCW-D 50 Rear View



SUPPLIED ACCESSORIES

- 1 Power cable
- 1 serial null modem cable
- MCW-D 50 Conference Software, incl. base version of the Controller for 5 microphone units Order # 480.274

Note:
Delivery does not include any antennae.

OPTIONAL ACCESSORIES

- CA 2411 Angled rod antenna, 2.4 GHz Order # 464.236
 - CA 2412 Rod antenna, 2.4 GHz Order # 464.244
 - CA 2413 Planar antenna, 2.4 GHz Order # 464.252

 - CA 2420 Standard cable, 2.4 GHz, sale per metre Order # 464.260
 - CA 2421 Standard cable, 2.4 GHz, N(HF)-N(HF), 10 m Order # 464.279
 - CA 2422 Standard cable, 2.4 GHz, N(HF)-N(HF), 20 m Order # 464.287
 - CA 2430 Low attenuation cable, 2.4 GHz, sale per metre Order # 464.295
 - CA 2431 Low attenuation cable, 2.4 GHz, N(HF)-N(HF), 10 m Order # 464.309
 - CA 2432 Low attenuation cable, 2.4 GHz, N(HF)-N(HF), 20 m Order # 464.325
 - CA 2441 RT Antenna amplifier for transmitting and receiving, input level max. 6 dBm
(10 dB gain), remote power supply 5 V via antenna cable Order # 470.309
 - CA 2441 T Antenna amplifier for transmitting, input level 20 dBm (8 dB gain),
remote power supply 5 V via antenna cable Order # 470.317
 - CA 2442 Adapter N(HF) Female - SMA Male Order # 464.376
 - CA 2443 Adapter N(HF) Female - SMA Female Order # 464.384
 - CA 2444 Adapter N(HF) Male - SMA Female Order # 464.392
 - CA 2445 Adapter N(HF) Male - SMA Male Order # 465.151

 - CA 2457 Charger/DC power supply unit for MCW-D 5** microphone units Order # 479.721
- MCW-D 50 Controller
Licence for controller to control the system via PC Order # 480.262

ARCHITECT'S SPECIFICATIONS

Central control unit of a wireless digital discussion system. Specific DSSS modulation (Direct Sequence Spread Spectrum) ensures a high noise immunity in the 2.4 GHz frequency band world-wide approved. A virtually unlimited number of microphone units can be controlled. Up to 9 data channels allow the use of max. 9 audio-voice streams. Depending on the version of the control unit a maximum of 3 or 9 microphone units can be allocated simultaneously. Automatic audio channel allocation. Diversity technology ensures a high transmission safety. Operation modes: manual: each participant can switch his microphone on or off; voice-controlled allocation: as soon as someone speaks into the microphone it is switched on; override: when a microphone is activated, the first one will be switched off; Push-To-Talk: the microphone button must be held down while the participant is speaking. The complete system can be switched off with the stand-by button on the front or via a control command of the serial interface or the network connection. RS 232 serial interface / Ethernet interface for system configuration, PC or media control system. Audio input for external signals. All connections on the rear are plug-in types: audio master output (3-pin XLR, balanced, RCA, unbalanced), audio input (3-pin XLR balanced, RCA, unbalanced), antenna input A/B and antenna output (N-RF). 19" desktop housing, 2 HU. Dimensions (WxHxD) 440x88x310mm. Weight: 4.7 kg.

Manufacturer: beyerdynamic
Product: MCW-D 50